

LIVER DISEASE DETECTION USING CT IMAGES

G.Bhuvana(M.E), K.Radha M.E(ph.d)AP/CSE, Muthayammal Engineering College

E.Mailid: bhuvanait2012@gmail.com, kradhagokul@gmail.com

Mobileno:9150399059, 9842391220

Abstract:

Video Segmentation is an important research topic in image processing. Interactive image segmentation algorithms are sensitive to the user inputs and often unable to produce an accurate boundary with a small amount of user interaction. They frequently rely on laborious user editing to refine the segmentation boundary. The proposed method exhibits many desirable properties of an effective interactive image segmentation algorithm, including robustness to user inputs and different initializations, the ability to produce a smooth and accurate boundary contour, and the ability to handle topology changes. The proposed work is to find tumours, what type of disease and where it is affected in the liver using neural network classifier algorithm.

Index term: Sift, Neural network classifier

INTRODUCTION:

Segmentation of video with background has been important research topic in intelligent surveillance and human-machine interface technologies, etc. In general, interactive image segmentation algorithms can be classified into two categories: boundary-based approaches and region-based approaches. In boundary-based approaches, the user is often asked to specify an initial area that is "close" to the desirable boundary. The active contours/Snake method, attempts to evolve an initial contour toward the object boundary. Methods based upon intelligent scissors, apply Dijkstra's shortest path algorithm to find a path between boundary seed points specified by the user. Considering that the boundary-based approaches require great care to specify the boundary area or the boundary points, especially for complex shapes, most recent interactive image segmentation algorithms take the regional information as the input. In particular, in region-based approaches, the user is often asked to draw two types of strokes to label some pixels as foreground or background, after which the algorithm completes the labeling of all other pixels. liver tissue there are four pathologies that coexists. In this field liver biopsy is used as ground truth. Using biopsy these pathologies can be assessed.

Unfortunately liver biopsy is an invasive procedure with various side effects.


RELATED WORKS

First, region-based methods are overly sensitive to small variations in the interactions provided by the user (see Fig. 1). As pointed out in [1], the Graph Cut algorithm is sensitive to the number of seeds, while the RW and Geodesic algorithms are sensitive to locations of seeds.

Second, the boundaries generated by the region-based approaches, especially those generated by RW and Geodesics based approaches, are often jaggy and do not adhere to the geometric features in the image (see Fig. 1). Most of the state-of-the-art interactive image segmentation methods [2],[3], [4], [5] rely on additional user inputs to either globally or locally refine the boundary. However, when dealing with complex images, the user is often required to provide a lot of additional strokes or boundary points and thus struggles with laborious refinement/editing.

As previously noted, the classical active contour model [6] is primarily used to perform local contour adjustment to improve the smoothness. The geodesic active contour model proposed in [7] is capable of evolving the entire boundary contour to snap to geometry edges, but it

heavily depends on the edge detection function.



METHODOLOGY:

we describe the proposed constrained active contour method, which extends the convex active contour model of (1) (originally designed for automatic image segmentation) for interactive image segmentation.

A. Contour Initialization

For any active contour method, the contour needs to be initialized before the contour evolution process. Here, we use the segmentation result of the Geodesic method [5] for contour initialization due to its fast processing speed and the ability to avoid the “small-cut” problem. In particular, we represent the result of the Geodesic algorithm by a probability map $P(x)$, whose value is within the range of [0,1] indicating the probability that pixel x belongs to the foreground region. In the Geodesic algorithm, for a pixel x , its geodesic distances to the foreground or background seed regions are computed, which are denoted as $D_F(x)$ and $D_B(x)$ respectively. Then, an estimate of the probability that the pixel x belongs to the foreground is calculated as

$$P(x) = \frac{D_B(x)}{D_F(x) + D_B(x)}$$

B. Constrained Active Contour Model

As shown in (1), the convex active contour model consists of two terms: a regional term and a boundary term. Next, we discuss how to modify these two terms to incorporate the information from the user input and the initial segmentation result so as to ensure the refined contour complying with the user input.

1) Regional term formulation: The foreground and background seeds give an excellent description about the color distributions of the foreground and background regions.

Foreground/background GMMs introduced in [8] are estimated from foreground/background seeds and used to represent the color distributions of the foreground and background regions.

2) Boundary term formulation: The boundary term of


$$\int_{\Omega} g_b(x) |\nabla u| dx$$

is essentially a weighed total variation of function u , where the weight g_b plays an important role.

C. Liver Disease

- **Viral hepatitis** Caused by viruses that attack the liver, viral hepatitis comes in many forms. The most common forms world-wide are [hepatitis A, B and C](#). Although hepatitis A and B can be prevented by vaccine, there is no vaccine for hepatitis C. In Canada, hepatitis C is the leading cause of liver transplants.
- **Obesity** The leading cause of liver disease in Canada is [fatty liver disease](#) linked to obesity.
- **Alcohol** Factors such as gender, age, nationality, weight and health can affect how a person’s liver metabolizes alcohol. When the liver has too much alcohol to handle, normal liver function may be interrupted leading to a chemical imbalance. If the liver is required to detoxify alcohol continuously, liver cells may be destroyed or altered resulting in fat deposits (fatty liver) and more seriously, either inflammation (alcoholic hepatitis)

and/or permanent scarring (cirrhosis). [Liver cancer](#) can also result from alcohol induced liver disease.



D. Neural Network Classifier

A neural network consists of units (neurons), arranged in layers, which convert an input vector into some output. Each unit takes an input, applies a (often nonlinear) function to it and then passes the output on to the next layer. Generally the networks are defined to be feed-forward: a unit feeds its output to all the units on the next layer, but there is no feedback to the previous layer. Weightings are applied to the signals passing from one unit to another, and it is

these weightings which are tuned in the training phase to adapt a neural network to the particular problem at hand. This is the learning phase.

RESULT DISCUSSION

we have proposed a robust and accurate interactive image segmentation method based on the continuous domain convex active contour model. We have demonstrated that our method outperforms the state-of-the-art interactive segmentation methods. It exhibits many desirable properties for a good segmentation tool, including the robustness to user inputs and different initializations, the ability to produce a smooth and accurate boundary contour, and the ability to handle topology changes. Our method runs very fast due to the fact that the proposed constrained active contour model can be solved quickly by a fast Split Bergman method, and the adoption of the Geodesic algorithm for initialization. We would like to point out that although the proposed constrained active contour model was able to automatically optimize an initial contour, it can also take additional user inputs for further user-guided contour evolving. This was especially necessary in either the case that the initial contour is very poor or the case that a highly accurate result is sought. This paper can be extended in a few ways. For example, it might be beneficial to apply the continuous-domain convex active contour model for other segmentation problems, such as image matting or video segmentation. Also, it was interesting to adopt some advanced evaluation method, such as the user simulation-based approach proposed in [9] to fully evaluate the performance of different interactive image segmentation methods.

REFERENCES

- [1] A. Sinop and L. Grady, "A seeded image segmentation framework unifying graph cuts and random walker which yields a new algorithm," in IEEE ICCV, 2007, pp. 1–8

- [2] C. Rother, V. Kolmogorov, and A. Blake, "Grabcut: Interactive foreground extraction using iterated graph cuts," in ACM SIGGRAPH, 2004.
- [3] L. Grady, "Random walks for image segmentation," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 28, no. 11, pp. 1768–1783, 2006.
- [4] W. Yang, J. Cai, J. Zheng, and J. Luo, "User-friendly interactive image segmentation through unified combinatorial user inputs," *IEEE Transactions on Image Processing*, vol. 19, no. 9, pp. 2470–2479, Sept. 2010.
- [5] X. Bai and G. Sapiro, "A geodesic framework for fast interactive image and video segmentation and matting," in *IEEE ICCV*, 2007, pp. 1–8.
- [6] M. Kass, A. Witkin, and D. Terzopoulos, "Snakes: Active contour models," *IJCV*, vol. 1, no. 4, pp. 321–331, 1988.
- [7] V. Caselles, R. Kimmel, and G. Sapiro, "Geodesic active contours," *International journal of computer vision*, vol. 22, no. 1, pp. 61–79, 1997.
- [8] C. Yang, R. Duraiswami, N. Gumerov, and L. Davis, "Improved fast Gauss transform and efficient kernel density estimation," in *IEEE ICCV*, 2003, pp. 664–671.
- [9] K. McGuinness and N. E. O'Connor, "Toward automated evaluation of interactive segmentation," *Computer Vision and Image Understanding*, vol. 115, no. 6, pp. 868–884, 2011.
- [10] E. Mortensen and W. Barrett, "Interactive segmentation with intelligent scissors," *Graphical Models and Image Processing*, vol. 60, no. 5, pp. 349–384, 1998.
- [11] A. Falcao, J. Udupa, and F. Miyazawa, "An ultra-fast user-steered image segmentation paradigm: live wire on the fly," *Medical Imaging, IEEE Transactions on*, vol. 19, no. 1, pp. 55–62, 2002.
- [12] Y. Boykov and M. Jolly, "Interactive graph cuts for optimal boundary and region segmentation of objects in ND images," in *IEEE ICCV*, 2001, pp. 105–112.
- [13] J. Zhang, J. Zheng, and J. Cai, "A diffusion approach to seeded image segmentation," in *IEEE CVPR*, 2010.
- [14] A. Criminisi, T. Sharp, and A. Blake, "Geos: Geodesic image segmentation," *ECCV*, pp. 99–112, 2008.
- [15] F. Chan, F. Lam, P. Poon, H. Zhu, and K. Chan, "Object boundary location by region and contour deformation," *Vision, Image and Signal Processing, IEE Proceedings*, vol. 143, no. 6, pp. 353–360, 2002.
- [16] Bresson, X. et al., "Fast global minimization of the active contour/snake model," *Journal of Mathematical Imaging and Vision*, vol. 28, no. 2, pp. 151–167, 2007.
- [17] T. Chan and L. Vese, "Active contours without edges," *IEEE Transactions on Image Processing*, vol. 10, no. 2, pp. 266–277, 2001.
- [18] S. S. Kumar, R. S. Moni and J. Rajeesh, "Automatic Liver and Lesion Segmentation: A Primary Step in Diagnosis of Liver Diseases," *VSignal, Image and Video Processing*, 2011.
- [19] L. Ruskó, G. Bekes, G. Németh and M. Fidrich, "Fully Automatic Liver Segmentation for Contrast Enhanced CT Images," *MICCAI Wshp. 3D Segmentation in the Clinic: A Grand Challenge*, 2007, pp. 143-150.
- [20] C. M. Li, C. Y. Xu, C. F. Gui and M. D. Fox, "Distance Regularized Level Set Evolution and Its Application to Image Segmentation," *IEEE Transactions on Image Processing*, Vol. 19, No. 12, 2010, pp. 3243-3254.